

**PICCO LED S**


aluminum

9106



cut out ø 38 mm

IP67



**PAOLI**

steel, glass

9554

1xGU10, max 10W

cut out ø 100 mm

IP67




**MON LED**

aluminum, glass

4454

cut out ø 64 mm

IP67



**PICCO LED M**


aluminum

9105



cut out ø 55 mm

IP67



**PICCO LED L**


aluminum

9104



cut out ø 65 mm

IP67



**PAT LED**


aluminum, plastic PC

8162



cut out ø 56 mm

IP65



**CIRCLET LED**

aluminum, plastic PC

8163



cut out ø 57 mm

IP65

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9106	1W LED	3000K	47 lm	42°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0,55	IP67	10000h
9105	1W LED	3000K	52 lm	51°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0,55	IP67	10000h
9104	3W LED	3000K	130 lm	48°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0,55	IP67	10000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
4454	2W LED	3000K	100 lm	28°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0,42	IP67	10000h
8162	3W LED	3000K	12 lm	25°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0,5	IP65	10000h
8163	3W LED	3000K	120 lm	47°	≥ 80	~220-230 V, 50/60 Hz	⊕	>0,5	IP65	10000h